



P O B J E D A-RUDET d.d.
BOSNIA & HERZEGOVINA
Višegradaska bb. 73000 G O R A Ž D E



Dioničko društvo za proizvodnju i promet proizvoda za rudarstvo Pobjeda-Rudet d.d. Goražde
Company for production and sale of products for mining Pobjeda-Rudet d.d. Goražde

www.pobjeda.com

e-mail: info@pobjeda.com

TECHNICAL CHARACTERISTICS

Shock tube

Name	Shock tube
Typ	BIHNEL tube
Material initiating tube	Surlyn/Nucrel/HDPE
Intervall of delay	-
Explosive charge	HMX/Al
The color of initiating tube	green,yellow, red
Sensitivity to attack	Impassiveness pri udaru do 60 J
Pulse rate	1800-2000 m/s
Transmission of detonating in tube	4 cm (100%)
The force of interruption	160 N – 180 N
Stretching	Up to 250%
Resistance to mechanical damage	Meets standards EN 13765-5 ponit 5.2.1
Temperature area of using	-30°C < T < +60°C
The time of usage	2 years (-25°C up to +40°C)
The class of dangerous	1.4
Code	S
Classification code	1.4 S
UN No.	0500
Certificate; Notified body	CE mark, Number: 1395-017/2010 According to Directive 93/15 EC Konštrukta defence a.s.