



P O B J E D A-RUDET d.d.
BOSNIA & HERZEGOVINA
Višegradska bb. 73000 G O R A Ž D E



Dioničko društvo za proizvodnju i promet proizvoda za rudarstvo Pobjeda-Rudet d.d. Goražde
Company for production and sale of products for mining Pobjeda-Rudet d.d. Goražde

www.pobjeda.com

e-mail: info@pobjeda.com

TECHNICAL CHARACTERISTICS

Surface Connector BIHNEL SL

Name	Surface connector
Typ	BIHNEL SL
Shell material	Aluminium
Delay time	0ms, 17ms, 25ms, 33ms 42ms, 67ms, 109ms, 176ms
Secondary charge	0,3 g PETN
Primary charge	0,2 g Phlegmatic lead-azide
Constringency	Fourfold
The plug	The rubber cover
Connector stirring	The coloured plastic material
The capacity of initiating tube	8 pcs. initiating tube
Material initiating tube	Surlyn/Nucrel/HDPE
The color of initiating tube	Yellow
The length of initiating tube	Upon request of the buyer
The marking	Etiquette (typ of detonator, the time of delay)
The resistance to the static electricity	20kV, 500 pF
	1 kV AC/50 Hz/60s
The hermetic	0,2 MPa/24 h
The resistance on mechanical weight	40 N/ 2 min
Temperature area of using	-30°C < T < +60°C
The time of usage	2 years (-25°C do +40°C)
The class of dangerous	1.4
Code	S
Classification code	1.4 S
UN No.	0500
Certificate; Notified body	CE mark, Number: 1395-013/2010 According to Directive 93/15 EC Konštrukta defence a.s.